

Up to 3 Heat / 2 Cool Heat Pump Up to 2 Heat / 2 Cool Conventional Smart Wi-Fi Universal Thermostat



Thermostat Features

7205

- 7 Day, 5-2 Day or Non-Programmable
- Large 3 sq. in. Backlit Display
- Bright Blue Backlight
- Auto or Manual Changeover
- User and Installer Lock Modes
- SmartLimit[®] Temperature Limits
- Auxiliary Heat Fossil Fuel Option
- Hardwire or Battery Powered
- Circulating Fan Mode
- Wi-Fi works without common (C) wire on most systems; requires common on Heat Pump, Heat Only or Cool Only Systems

FREE Color Contractor Branding! Visit braeburnonline.com

Application Features

- · Compatible with Virtually All Smartphones, Tablets or PC's
- Multi-Color Program Groups Simplify Scheduling
- Flexible Vacation and Holiday Scheduling
- Text and E-Mail Service and Temperature Alerts
- BlueLink QuickCopy® Allows User to Duplicate Program and Configuration to Other Thermostats
- QuickEdit®Makes Schedule Changes Easy
- BlueLink SmartData[®] Energy Report Capability
- Monitor and Control Multiple Thermostats
- Easy Access Dealer Information
- Optional Geofencing for Increased Energy Savings

App Store Google Play

Compatible with Amazon Alexa Amazon Alexa is a trademark of Amazon.com, Inc.



works with the Google Assistant

www.braeburnonline.com

Toll-Free 866.268.5599 (U.S.) +1.630.844.1968 (Outside the U.S.)





BlueLink Smart Connect Application Screens

FREE app to monitor and control multiple thermostats from virtually any Smartphone, Tablet or PC

Multi-Color Program Groups Vacation and Holiday Scheduling Geofencing BlueLink BlueLink lueLink 0 USE SCHEDULE SCHEDULE 1 × (TR) BlueLink QuickCopy® Feature **BlueLink SmartData® Reports** eLink eLink BlueLink Main Fi





Service and Temperature Alerts





BlueLink Service Connect Application Screens

FREE app for contractors, allowing them the ability to monitor and manage multiple customer thermostats



Product Specifications

Dimensions:	3.70" x 5.2" x 1.38"
Electric Rating:	24 Volt AC (18-30 Volt AC) 1 amp maximum load per terminal 5 amp total maximum load (all terminals)
AC Power:	18-30 Volt AC
DC Power:	3.0 Volts DC (2 "AA" Alkaline batteries included)
To Use Wi-Fi:	Wi-Fi works without common (C) wire on most systems; requires common on Heat Pump, Heat Only or Cool Only Systems
Compatibility:	Heat pump systems up to 3 heat/2 cool, Conventional systems up to 2 heat/2 cool
Wi-Fi Communication:	802.11
Control Range:	45° to 90° F (7° to 32° C)
Display Range:	40° to 99° F (5° to 37° C)
Accuracy:	+/- 1° F (+/5° C)
Terminations:	Rh, Rc, C, W2, W1/E/W3, O/B, G, Y2, Y1, K

Link ?

Shipping Information

INDIVIDUAL CARTON Dimensions: 4.5" x 5.75" x 2.25" Weight: 1.0 lbs.



MASTER CARTON Quantity: 3 **Dimensions:** 7.15" x 6" x 4.7" Cubic Feet: 14 Weight: 3.25 lbs.

Braeburn 7205 Replaces*

Honeywell® TH8732WF, TH6220WF Emerson[®] 1F86U-42WF

Pro1° T855i, T701i Nest° T100577, T200577, T3007ES

*Verify specific application requirements. All trademarks are the property of their respective owners.

Accessories

7340 Share-a-Wire® Module 5970 Universal Thermostat Guard 2920 Vertical J-Box Adapter Wall Plate (6.5" x 5.1") 2950 Universal Wall Plate (6.5" x 6.5")



Visit our website (www.braeburnonline.com) for more information, contact your local distributor Branding Available! or call our sales department toll-free at 866.268.5599 (U.S.), +1.630.844.1968 (Outside the U.S.).



Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google and Google Play are trademarks of Google LLC. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates