

D and HD Series

2-Wire Round/Rectangular Zone Dampers

D-XX
HD-XXXX

The D Series dampers are galvanized steel, single-blade dampers with a 24 volt spring return actuator. These dampers are shipped complete and ready for installation. They are rated for duct systems with less than 1.0" WC. The D Series damper has a simple adjustment for setting the minimum position.



Features and Benefits:

- Compatible with most zone control panels
- 24-gauge steel shell
- 24 volt synchronous motor
- Quiet operation
- Simple adjustment for setting the minimum position

Warranty: 5 years

Can be configured as PC/SO or PO/SC

Specifications:

Construction	24-gauge steel shell
Sizes	5", 6", 7", 8", 9", 10", 12", 14", 16", 18"
Damper Actuator Type	24VAC, 10VA, two-wire power close/spring open

The HD Series dampers are extruded aluminum parallel blade dampers with a 24 volt spring return actuator. These dampers are shipped complete and ready for installation. The HD Series dampers can be installed in any position. They are rated for duct systems with less than 1.0" WC. The damper has a simple adjustment for setting the minimum position.



Features and Benefits:

- Compatible with most zone control panels
- Extruded aluminum
- 24 volt synchronous motor
- Quiet operation
- Simple adjustment for setting the minimum position

Warranty: 5 years

Can be configured as PC/SO or PO/SC

Specifications:

Construction	Extruded aluminum
Sizes	6" x 6" to 36" x 24" side-mount or bottom-mount motor
Damper Actuator Type	24VAC, 10VA, two-wire power close/spring open