

# HE-6800 Series Humidity Transmitters with Temperature Sensor Catalog Page

## Description

The HE-6800 Series Humidity Transmitters with Temperature Sensor provide both humidity and temperature sensing in room wall-mount applications. The transmitter offers local warmer/cooler temperature setpoint adjustment and temporary occupancy override. The humidity sensor provides Relative Humidity (RH) accuracy of  $\pm 2\%$  or  $\pm 3\%$  RH and measures RH over the entire range of 0 to 100%.

A warmer/cooler dial is included on certain models for minor temperature adjustments from the setpoint. All models feature an occupancy override button that allows the user to override time-of-day scheduling when the space is occupied outside of the normal occupied hours schedule. The transmitter also includes DIP switches to enable or disable override and Light-Emitting Diode (LED) functions. In addition, all models feature a user-selectable 0 to 5 VDC or 0 to 10 VDC humidity output switch, and a power supply selection switch.

The HE-6800 Series Humidity Transmitters include screw terminal block terminations that provide flexibility for field wiring. All models include a 6-pin modular jack access port for connecting accessories to the Zone Bus. This feature allows a technician to commission or service the controller via the transmitter.

## Features

- controller configuration DIP switch — allows users to adjust the room comfort and choose occupancy features that match the application and transmitter
- power supply selection switch — enables transmitter use in high input voltage applications
- user-selectable humidity output — provides either a 0 to 5 VDC or 0 to 10 VDC output for compatibility with various controllers



HE-6800 Series Humidity Transmitters with Temperature Sensor

- occupancy Light-Emitting Diode (LED) indicator — displays the current operating mode of the controller (VMA12 and VMA14 Series only)
- manual override pushbutton (PB) — overrides time-of-day scheduling when the space is occupied outside of the normal occupied hours schedule
- warmer/cooler setpoint dial (select models) — allows for minor temperature adjustments from the setpoint

## Repair Information

If the HE-6800 Series Humidity Transmitter fails to operate within its specifications, replace the unit. For a replacement transmitter, contact the nearest Johnson Controls® representative.

## Selection Charts

### HE-6800 Series Humidity Transmitter with Temperature Sensor Product Code Numbers

Product Code Number	Temperature Sensing Element	Humidity Accuracy (% RH)	Warmer/Cooler Temperature Setpoint Adjustment Override	Enclosure Dimensions (mm)
HE-68N2-0N00WS	Nickel	$\pm 2\%$	No	80 x 80
HE-68N3-0N00WS	Nickel	$\pm 3\%$	No	80 x 80
HE-68N2-1N00WS	Nickel	$\pm 2\%$	Yes	80 x 80
HE-68N3-1N00WS	Nickel	$\pm 3\%$	Yes	80 x 80
HE-68P2-0N00WS	Platinum	$\pm 2\%$	No	80 x 80
HE-68P3-0N00WS	Platinum	$\pm 3\%$	No	80 x 80
HE-68P2-1N00WS	Platinum	$\pm 2\%$	Yes	80 x 80
HE-68P3-1N00WS	Platinum	$\pm 3\%$	Yes	80 x 80
HE-6863-0N00WS	10,000 Thermistor	$\pm 3\%$	No	80 x 80
HE-6863-1N00WS	10,000 Thermistor	$\pm 3\%$	Yes	80 x 80

### Optional Accessories

Product Code Number	Description
ACC-INSL-0 <sup>1</sup>	Wallbox Mounting Pad (10 per Bag)
ACC-INSL-1 <sup>1</sup>	Surface Mounting Pad (10 per Bag)
NS-WALLPLATE-0	Adapts an HE-6800 Series Humidity Transmitter (3-3/16 x 3-3/16 in. [80 x 80 mm]) to a Standard 3-3/16 x 4-3/4 in. (80 x 120 mm) Wallbox
T-4000-119	Allen-Head Adjustment Tool (30 per Bag)

1. These foam pads help prevent drafts from entering the unit through the wall, and make installation easier when mounting on an uneven surface.

## HE-6800 Series Humidity Transmitters with Temperature Sensor Catalog Page (Continued)

### Technical Specifications

HE-6800 Series Humidity Transmitters with Temperature Sensor			
<b>Power Requirements</b>		4.5 to 7.5 mA at 14 to 30 VDC and 5K ohm Load, or 18 to 25 mA at 20 to 30 VAC and 5K ohm Load	
<b>Terminations</b>		9-Position Screw Clamp Terminal Block	
<b>Wire Size</b>		16 to 24 AWG (1.3 to 0.6 mm Diameter); 18 AWG (1.0 mm Diameter) Recommended	
<b>Temperature Measurement Range</b>		32 to 131°F (0 to 55°C)	
<b>Humidity Measurement Range</b>	<b>Full Range</b>	0 to 100% RH	
	<b>Calibrated Range</b>	10 to 90% RH	
<b>Temperature Sensor</b>	<b>Nickel (HE-68Nx Models)</b>	<b>Sensor Type</b>	1,000 ohm Thin Film Nickel
		<b>Coefficient</b>	Approximately 3 ohm per F° (5.4 ohm per C°)
		<b>Reference Resistance</b>	1,000 ohm at 70°F (0°C)
		<b>Accuracy</b>	±0.34F° at 70°F (±0.18C° at 21°C)
	<b>Platinum (HE-68Px Models)</b>	<b>Sensor Type</b>	1,000 ohm Thin Film Platinum
		<b>Coefficient</b>	Approximately 2 ohm per F° (3.9 ohm per C°)
		<b>Reference Resistance</b>	1,000 ohm at 32°F (0°C)
		<b>Accuracy</b>	±0.35F° at 70°F (±0.19C° at 21°C)
	<b>Nonlinear NTC, Thermistor, Type II (HE-686x Models)</b>	<b>Sensor Type</b>	10,000 ohm NTC Thermistor
<b>Coefficient</b>		Nonlinear NTC, Johnson Controls Type II	
<b>Reference Resistance</b>		10,000 ohm at 77°F (25°C)	
<b>Accuracy</b>		±0.9F° (±0.5C°) at 32 to 158°F (0 to 70°C)	
<b>Humidity Sensor Type</b>		Capacitive Polymer Sensor	
<b>Humidity Element Accuracy</b>	<b>HE-68x2 Models</b>	±2% RH for 20 to 80% RH at 50 to 95°F (10 to 35°C); ±4% RH for 10 to 20% RH and 80 to 90% RH at 50 to 95°F (10 to 35°C)	
	<b>HE-68x3 Models</b>	±3% RH for 20 to 80% RH at 77°F (25°C); ±6% RH for 10 to 20% RH and 80 to 90% at 77°F (25°C)	
<b>Setpoint</b>	<b>Range</b>	Warmer/Cooler	
	<b>Resistance</b>	1500 Ohms	
<b>Temperature Sensor Time Constant</b>		10 Minutes at 10 ft per Minute	
<b>Manual Override</b>		Integral Momentary Pushbutton (DIP Switch Selectable)	
<b>LED</b>		Green LED Indicates Three Modes of Operation (VMA12 and VMA14 Series Controllers Only)	
<b>Ambient Operating Conditions</b>		32 to 131°F (0 to 55°C), 10 to 95% RH Noncondensing; 86°F (30°C) Maximum Dew Point	
<b>Ambient Storage Conditions</b>		-40 to 140°F (-40 to 60°C), 5 to 95% RH Noncondensing; 86°F (30°C) Maximum Dew Point	
<b>Materials</b>		White Thermoplastic Protection: IP30 (EN 60529)	
<b>Dimensions (H x W x D)</b>	<b>HE-68xx-0 Models</b>	3-3/16 x 3-3/16 x 1-5/16 in. (80 x 80 x 32 mm)	
	<b>HE-68xx-1 Models</b>	3-3/16 x 3-3/16 x 1-7/16 in. (80 x 80 x 35 mm)	
<b>Shipping Weight</b>		0.44 lb (0.20 kg)	
<b>Compliance</b>	<b>United States</b>	UL Listed, File E107041, CCN PAZX, Under UL 916, Energy Management Equipment	
	<b>Canada</b>	UL Listed, File E107041, CCN PAZX7, Under CAN/CSA C22.2 No. 205, Signal Equipment	
	<b>Europe</b>	CE Mark – Johnson Controls, Inc., declares that this product is in compliance with the essential requirements and other relevant provisions of the EMC Directive 2004/108/EC. WEEE Directive 2002/96/EC RoHS Directive 2002/95/EC	
	<b>Australia and New Zealand</b>	C-Tick Mark, Australia/NZ Emissions Compliant	